Specification Table

		27 Inch
	Resolution	1080x1920
Panel	Display Area (mm)	336.2x597.6
	Pixel Pitch (mm)	0.3114x0.3114
	Aspect Ratio	16:9
	Viewing Angle	178°
	Colour	16.7M
	Contrast Ratio	5000:1
	Brightness (cd/m²)	350
	Response time	5ms
	Lifespan (hours)	70,000
Touch	Touch Technology	Projected Capacitive
	Touch Points	10
	Glass Hardness	6H minimum
Audio	Built-in stereo speakers	8Ω,5W×2
taato	Power Consumption (W)	65, 5W X Z
Power		
	Power Input	AC110~240V (50Hz~60Hz) 462x1075x192.4
Mechanical	Unit Size (WxHxD mm)	
	Package Size (WxHxD mm)	1155x560x265
	Mounting Holes (mm)	350x900
	Net Weight (kg)	41
	Gross Weight (kg)	45
	Card Machine Slot Size (WxH mm)	92x193
Environmental	Operating Temperature	0°C to 50°C
	Storage Temperature	-30°C to 60°C
	Operating Humidity	10% to 80%
	Storage Humidity	5% to 95%
Computer	CPU	Intel Core i5-8259U (2.3GHz (3.8GHz Boost) Quad Core)
	RAM	8GB DDR4 (2666MHz Expandable to 32GB Dual Slot)
	Hard Drive/Internal Memory	256GB M.2 SSD
	LAN	10/100/1000 Ethernet
	Wi-Fi	Dual-Band 5GHz/2.4GHz 802.11n/ac
	OS	Windows 7, Windows 8, Windows 10, Linux (licence purchased separately)
Printer	Printing Method	LineThermal
	Available Printing Width	58mm or 80mm
	Printing Speed	Max. 250mm/s
Scanner	Sensing Mode	CMOS
	Light Source	LED (6000K) 900lux @100mm
	Scanning Angle	Omni-directional
	Scanning Speed	30 times/second
	Resolving Power	640x480 pixels
	Reading Accuracy	≥8mil
	Print Contrast	≥20%
Accessories	Included	Till Roll Key, Front Access Key, User Manual, Wi-Fi Aerial, Power Cable
	Optional	Floor Stand, Software Package
Standards	Certification	CE,FCC & ROHS
Warranty	Warranty Period	3 Year Warranty
	Technical Support	Lifetime

Errors and omissions excepted





