BenQ 65" Interactive Display(9H.F9STB.DE1)

BenQ Board Essential RE6503A - 65" Diagonal Class RE03A Series LED-backlit LCD display education - with built-in interactive whiteboard, touchscreen (multi touch) - 4K UHD (2160p) 3840 x 2160



Main Specifications

Product Description	BenQ Board Essential RE6503A RE03A Series - 65" LED-backlit LCD display - 4K - for education			
Product Type	LED-backlit LCD flat panel display with built-in interactive whiteboard, touchscreen (multi touch)			
Diagonal Class	65"			
Commercial Use	Yes - education			
Resolution	3840 x 2160			
Display Format	4K UHD (2160p)			
Video Interface	HDMI			
HDMI Ports Qty	3 ports			
Connectivity	Wi-Fi, LAN, Bluetooth			
PC Interface	VGA (HD-15), DisplayPort			
Technology	IPS			
LCD Backlight Technology	LED backlight			
Image Aspect Ratio	16:9			
TV Tuner	No tuner			
Commercial Features	OPS Slot			
Picture Enhancements	72% Colour Gamut NTSC			
Speaker System	2 speakers			
Storage Capacity	32 GB			
USB	5 ports			
Included Accessories	Remote control, 2 styluses			
Voltage	AC 100-240 V (50/60 Hz)			
Power Consumption Operational	124 Watt			
Power Consumption Stand by	0.5 Watt			
Dimensions (WxDxH)	148.45 cm x 9 cm x 90.81 cm			
Weight	38.6 kg			
Environmental Standards	ENERGY STAR Qualified			

Extended Specification

Product Type	LED-backlit LCD flat panel display			
Power Consumption Operational	124 Watt			
Diagonal Class	65"			
Commercial Use	Yes - education			
Combined With	Built-in interactive whiteboard, touchscreen (multi touch)			
Series	RE03A Series			
Operating System	Android OS 11.0			
TV Tuner	No tuner			
TV Tuner Presence	No			
Sensors	Ambient light sensor (ALS), Infrared (IR)			
Video Interface	HDMI			
HDMI Ports Qty	3 ports			
PC Interface	VGA (HD-15), DisplayPort			
Modes	Landscape mode			
Picture Enhancements	72% Colour Gamut NTSC			
Protection	Germ-resistant			
Width	148.45 cm			
Depth	9 cm			
Height	90.81 cm			
Weight	38.6 kg			
Display				
LCD Display Technology	IPS			
Resolution	3840 x 2160			
Display Format	4K UHD (2160p)			
Image Aspect Ratio	16:9			
LCD Backlight Technology	LED backlight			
Coating	Anti-glare, 9H Hard			
Image Contrast Ratio	1200:1			
Dynamic Contrast Ratio	30000:1			
Brightness	450 cd/m ²			
Touchpoints Qty	40			
Response Time	8 ms			
Backlight Life	50,000 hour(s)			
Commercial Features	OPS Slot			
Features	Infrared touch technology, EZWrite Software, 10-bit support, Over-the-Air Update (OTA), Account Management System (AMS), Device Management Solution (DMS), precision touch technology, BenQ ClassroomCare solutions			

Stands & Mounts

Wall Mount Included	Yes
Flat Panel Mount Interface	600 x 400 mm
VESA Compatibility	Yes

Media Player

USB Port	Yes
USB Ports Qty	5
Configuration	ARM Cortex-A55 Quad-Core - 4 GB - 32 GB - Mali-G52 2EE MC1

Remote Control

Туре	Remote control
Audio System	
Speaker System	2 speakers
Output Power / Total	40 Watt
Speakers	2 x main channel speaker - 20 Watt

Network & Internet Multimedia

Connectivity	Wi-Fi, LAN, Bluetooth
LAN Protocol	Gigabit Ethernet
Connect & Share	InstaShare 2

Connections

	3 x HDMI input
	VGA input DisplayPort 3 x USB 3.0 USB 2.0
Connector Type	USB 2.0 USB-C 2.0 2 x touch Audio line-in Audio line-out SPDIF output Gigabit LAN RS-232

Miscellaneous

Included Accessories	2 styluses
Cables Included	VGA cable - 3 m HDMI cable - 3 m USB touch cable - 3 m USB-C cable - 1.5 m
Compliant Standards	TUV Rheinland Low Blue Light Certification, TUV Rheinland Flicker Free Certification
Sustainability Information	
ENERGY STAR Certified	Yes
ENERGY STAR Version	8.0
Power	
Power Device	Power supply

Power Device	Power supply
Input Voltage	AC 100-240 V (50/60 Hz)
Power Consumption Stand by	0.5 Watt

Dimensions & Weight (Shipping)

Width (Shipping)	166.5 cm		
Depth (Shipping)	22.5 cm		
Height (Shipping)	104 cm		
Weight (Shipping)	51.9 kg		
Environmental Parameters			
	0.80		

Min Operating Temperature	
Max Operating Temperature	40 °C
Humidity Range Operating	20 - 85% RH (non-condensing)

Product data is provided by CNET, we do not warrant the accuracy and completeness of the material contained in this data sheet