




Specifications

Model		IFP6552-1A/IFP6552-1B	IFP7552-1A/IFP7552-1B	IFP8652-1A/IFP8652-1B
Model				
Display	Panel Size	65"	75"	86"
	Type/Tech	TFT LCD Module with DLED Backlight.		
	Aspect Ratio	16:9		
	Native Resolution	UHD 3840 x 2160 (Pixels)		
	Brightness	400 nits (typ.)		
	Contrast Ratio	1200:1 Typ. , 5000:1 Max.(DCR enable)		
	Response Time	8ms		
	Viewing Angles	H = 178, V = 178 typ.		
	Backlight Life	50,000 Hours (Typ.)		
Platform	Surface Treatment	Hardness: 7H Anti glare + Anti fingerprint coating		
	Processor	ARM Cortex A73*4		
	RAM	LPDDR4: 4GB (IFP6552-1A) 8GB (IFP6552-1B)	LPDDR4: 4GB (IFP7552-1A) 8GB (IFP7552-1B)	LPDDR4: 4GB (IFP8652-1A) 8GB (IFP8652-1B)
Touch	Storage	32GB (IFP6552-1A) 64GB (IFP6552-1B)	32GB (IFP7552-1A) 64GB (IFP7552-1B)	32GB (IFP8652-1A) 64GB (IFP8652-1B)
	Type / Tech	UFT (Ultra-Fine Touch) Technology		
	Touch Point	Windows: 33 points touch / Android: 20 points touch		
	Response Time	≤10ms	≤10ms	≤11ms
	Scan rate	≥100HZ	≥100HZ	≥90HZ
	Accuracy size	+/- 1mm		
	Pen tips size	2.5mm/8mm		
	Palm resistant	YES		
	INPUT	HDMI-IN	x3	
RGB / VGA		x1		
DisplayPort		x1		
Audio		x1 (PC audio in)		
RS232		x1		
OPS		x1		
HDMI-OUT		x1		
Audio	x1 (Earphone out)			
SPDIF	x1 (optical)			
LAN	RJ45	x1		
USB	Type A	USB 2.0 x1; USB 3.0 x4		
	Type B	x2, for touch		
	Type C	Power Delivery 60W PD / DP1.2 / 100M Ethernet/USB3.0		
SPEAKERS		15W x 2 + 15W x 1 subwoofer		
Microphone		8 array microphone		
Embedded OS		Android 9		
Bundle Software	Basic Annotation Software	myViewBoard Whiteboard		
	Pro Annotation Software	myViewBoard whiteboard for Windows (embedded in Optional VPC)		
	Wireless Casting	ViewBoard Cast / MyViewBoard Display		
	Remote Device Management	myViewBoard Manager		

Model		IFP6552-1A/IFP6552-1B	IFP7552-1A/IFP7552-1B	IFP8652-1A/IFP8652-1B
Special Features	SmartPort™ USB	USB 3.0 port (auto switch between ViewBoard/PC/External laptop)		
	BYOM	Share AV USB-peripherals to external laptop via USB-C or Touch USB cable		
	Windows ink	Yes		
	LAN sharing between ViewBoard & PC	10/100/1000M for ViewBoard/PC source, 100M for USB-C		
	Light sensor	Yes		
	Flicker Free	Yes (in every brightness level)		
Power	Voltage	100-240VAC +/- 10% Wide Range		
	Consumption	190W (Typ.) < 0.5 W ("Off")	227W (Typ.) < 0.5 W ("Off")	332W (Typ.) < 0.5 W ("Off")
	Wall Mount (VESA®)	600 x 400	800 x 400	800 x 600
OPERATING CONDITIONS	Temperature (°C)	0°C to 40°C		
	Humidity	20% ~ 80% RH Non-Condensing		
DIMENSIONS (W x H x D)	Physical (inch / mm)	1509.1 (W) x 955.4 (H) x 119.1 (D) mm 59.41 (W) x 37.61 (H) x 4.69 (D) inch	1720.1 (W) x 1069.6 (H) x 118.4 (D) mm 67.72 (W) x 42.11 (H) x 4.66 (D) inch	1966.4 (W) x 1204.4 (H) x 118.4 (D) mm 77.42 (W) x 47.42 (H) x 4.66 (D) inch
	Packaging (inch / mm)	1660 (W) x 1045 (H) x 245 (D) mm 65.35 (W) x 41.14 (H) x 9.65 (D) inch	1880 (W) x 1160 (H) x 280 (D) mm 74.02 (W) x 45.67 (H) x 11.02 (D) inch	2140 (W) x 1340 (H) x 280 (D) mm 84.25 (W) x 52.76 (H) x 11.02 (D) inch
WEIGHT	Net (lb / kg)	96.78 lb / 43.9 kg	125.22 lb / 56.8 kg	156.53 lb / 71.0 kg
	Gross (lb / kg)	122.14 lb / 55.4 kg	158.95 lb / 72.1 kg	196.43 lb / 89.1 kg
REGULATIONS		cTUVus, FCC, EPEAT, Mexico coc, Mexico Energy, RoHS, Energy Star 8, CEC,EMC/CE, CB, RoHS & DOC, REACH, WEEE, ErP, EEL,RCM, BIS, PSE, VCCI,CCC, CECP	cTUVus, FCC, EPEAT, Mexico coc, Mexico Energy, RoHS, Energy Star 8, CEC,EMC/CE, CB, RoHS & DOC, REACH, WEEE, ErP, EEL,RCM, BIS, PSE, VCCI, BSMI,CC, CECP	cTUVus, FCC, EPEAT, Mexico coc, Mexico Energy, RoHS, Energy Star 8, CEC,EMC/CE, CB, RoHS & DOC, REACH, WEEE, ErP, EEL,RCM, BIS, PSE, VCCI, BSMI, CCC, CECP
Low Blue light (LBL certificate)		Yes		
Energy Star version		ES8.0		
EEL rating		A+		
PACKAGE CONTENTS		<ol style="list-style-type: none"> Power cable (3 meters) Remote control USB Type-C cable (1.5 meters) USB Touch cable (3 meters, USB2.0) Touch pen x 2 Quick Start Guide + Compliance statement RS232 adapter Clamp x 5 Camera Plate Screw x 8 (camera 2+2, wall mount 4) HDMI cable (3 meters) Eraser AAA Battery x 2 	<ol style="list-style-type: none"> Power cable (3 meters) Remote control USB Type-C cable (1.5 meters) USB Touch cable (3 meters, USB2.0) Touch pen x 2 Quick Start Guide + Compliance statement RS232 adapter Clamp x 5 Camera Plate Screw x 8 (camera 2+2, wall mount 4) HDMI cable (3 meters) Eraser AAA Battery x 2 	<ol style="list-style-type: none"> Power cable (3 meters) Remote control USB Type-C cable (1.5 meters) USB Touch cable (3 meters, USB2.0) Touch pen x 2 Quick Start Guide + Compliance statement RS232 adapter Clamp x 5 Camera Plate Screw x 8 (camera 2+2, wall mount 4) HDMI cable (3 meters) Eraser AAA Battery x 2