

# **Novo**Touch BK650i, BK750i, BK860i



The NovoTouch BK series is a 4K-UHD collaborative touch display solution that is perfect for education, but also for business meetings, available in 65", 75", and 86" display sizes.

The NovoConnect Wireless Collaboration will make it easy for any participant to share their device screen on the NovoTouch BK display.


The digital whiteboard function completes the classroom experience with a flawless touch annotation for a truly interactive session.





Call on 020 8795 3882





## **Key Features**



NovoConnect Wireless Collaboration

The BK series has built-in NovoConnect Lite wireless presentation and collaborative tools for cable-free and hassle-free presenting in the classroom or in the office.

Up to 8 participants can be connected and 2 can share their screen, each in 1080p resolution.




World Class Security- AES-256 Encryption, Password Protected, Dual Network Environment, ISO 27001 Certified.



### **Digital Whiteboard**

The BK series supports 40-point interactive touch capability. The digital whiteboard enables flawless annotation, highlighting and screen capture for easy sharing.





# **Novo**Touch

BK650i, BK750i, BK860i



#### **Google Play enabled**

Easy access to any Google Play app allows for even more flexible use and optimized working and teaching in any session.





## **4K UHD Resolution and rich connectivity** The BK series 65" / 75" / 86" display size with 4K Ultra-HD (3,840 x 2,160) resolution to deliver outstanding details and stunning visuals.

The multiple interfaces, such as USB Type-C, HDMI and USB2.0/3.0 allow easy connection to various devices.





#### Backlit D-LED Technology

Backlit D-LED (IPS panel) with Optical Bonding technology delivers brighter pictures, flawless colors, richer textures, and extra wide viewing angles (178°/ 178°). The result is incredibly sharp and crisp images.





#### **Eye Protection Technology**

The BK series is TÜV Rheinland Certified to ensure the best eye projection with low Blue Light & Flicker Free feature for the best viewing experience.





# **Product Specifications**

	M	odel Name	BK650i	BK750i	BK860i
Display	Panel Size		65"	75"	86"
	Type/Technology		Backlit D-LED (IPS- Panel)		
	Brightness		450 cd/m2		
	Contrast Ratio		5000:1		
	Native Resolution		4K Ultra-HD (3840 x 2160)		
	Viewing Angle (H/V)		178° / 178°		
	Aspect Ratio		16:9		
	Refresh Rate (Hz)		60 Hz		
	Estimated Life Time		50,000 Hours (Min)		
	Display Color (Bit)		1.07 Billion (10-bit)		
	Installation Orientation		Landscape		
	Daily Operation				
	(Hours/Days)		16/7		
Touch	Technology		Infrared Touch		
	Touch	Annotation	10 Points		
	Points	Touch	40 Points		
	Accuracy	Passive Pen	±2mm (Over 90% area)		
		Touch	±2mm (Over 90% area)		
	Touch Resolution		32,768 x 32,768		
	Surface Protection		4mm Thick Toughened Glass (Level 7H on Mohs Scale of Mineral Hardness)		
	Touch Tools		Finger, Stylus, Glove, Opaque Objects		
Operating System	System Version		Android™ v9.0		
	Internal Storage		32GB (eMMC Flash) (About 25GB User Availability)		
	Input	Display	HDMI v2.0 x3, VGA-In x1, Display Port 1.2 x1, AV(3.5mm) x1, YPbPr(3.5mm) x1		
	mpar	Audio	Audio-In (3.5mm) x1, Mic(3.5mm) x1		
	Output	Display	HDMI-Out v2.0 x1		
	Audio		Audio-Out (3.5mm) x1, SPDIF-Out x1		
	Internet		LAN (RJ45) x2		
	Control		RS232-In x1		
	Wireless (USB Dongle)		WiFi 5, IEEE802.11a/b/g/n/ac (2.4GHz/5GHz) WiFi 6, IEEE802.11ax (2.4GHz/5GHz) (optional)		
	USB		Front: USB-A 3.0 x3, Side:USB-A 3.0 x1, USB-A 2.0 x1, USB-B x5 (For Touch Port) USB-C 3.1 (15W power) x1		
Default Apps	Collaboration		Screen mirroring (NovoConnect Lite version), Education or Corporate mode, Digital Whiteboard,		
			WPS Office, Finder		
Expansion	Windows (OPS )		Intel Standard 80 Pin OPS- Optional		
Audio	Speakers		16W x2 (Stereo)		
Device Management	Software		Free Software- Remote Manager		
Power	Power Supply (Internal)		AC 100 - 240V, 50/60Hz (3.0A)	AC 100 - 240V, 50/60Hz (4.0A)	AC 100 - 240V, 50/60Hz (4.5A)
	Consumption		≤220W	≤330W	≤410W
	Standby Mode			<0.5W (Standby)	
	Dimension (L x H x D)mm		1523 x 945 x 107	1744 x 1070 x 107	1990 x 1208 x 107
Physical	Weight		45kg	62kg	76kg
Characteristics	VESA Mounting (FPMPMI)		4 – M8 × 25mm, 600 x 400mm (23.6" x 15.7")	4 - M8 × 25mm, 800 x	400mm (31.5" x 15.7")
	Color		Silver		
Accessories	Standard		AC Power Cord, Stylus (x2), Remote Control (W/Batteries), WiFi USB Module, Documentation Kit		
	Optional		WiFi 6 USB Dongle, LauncherPlus WQL400, LauncherPlusQL300, LauncherOne, HDMI Cable,		
Warranty	Standard		USB Cable(Touch), VGA Cable, Audio Cable, Wall Mount Kit 3-Year warranty on the panel		
	Education		5-Year warranty on the panel, where end customer is a school, university or training center. Education product registration required within 180 days of purchase for extended warranty to be valid.		

#### www.vivitek.eu | www.novoconnect.eu

©2022 Vivitek. Vivitek is a trademark of Delta Electronics, Inc. Other trademarks are the properties of their respective owners. Values, weights and dimensions shown are approximate. Errors and omissions accepted. Specifications are subjection to change without prior notice. Reference number: 09/2022

A brand of 🛕 NELTA



## Call on 020 8795 3882

www.goeducation.co.uk